



FUEL LINE HOSE

PRODUCT TYPE: FUEL SYSTEM

RECOMMENDED FOR: Clamped hose applications on all fuel systems, including fuel injection systems. Specially designed for fuel circuits (leaded and unleaded petrol, diesel) in passenger cars. Approved for transportation of B-7, E-5, E-10, E-15, low sulfur diesel.

RESISTANT TO: Tube resists heat and oil. Cover resists heat, oil, ozone and weathering.

CONSTRUCTION: **SHAPE:** Straight

TUBE: Nitrile (NBR)

REINFORCEMENT: Textile

WIRE: -



COVER: Nitrile (NBR) / PVC

STANDARDS: **SAE NORM** SAE J30R7

DIN NORM DIN 73379, except tolerances



TEMPERATURE:



	PN								
		mm	"	mm	m	mm	bar	bar	mm/HG
FL3.2X15	3225-00050	3.2	7/64	8	15	71	7.5	30	608
FL4X15	3225-00051	4	5/32	9	15	75	7.5	30	608
FL5X15	3225-00055	5	13/64	10	15	76	7.5	30	608
FL6X15	3225-00052	6	1/4	12	15	79	7.5	30	608
FL7X15	3225-00056	7	9/32	13	15	89	7.5	30	608
FL8X15	3225-00053	8	5/16	14	15	91	7.5	30	608
FL10X10	3225-00054	10	3/8	16	10	114	7.5	30	608
FL10X15	3225-10014*	10	3/8	16	15	114	7.5	30	608
FL12X15	3225-10015*	12	15/32	19	15	127	7.5	30	608

* boxed, not reeled